SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Contact Spray
UFI: H7FJ-72WY-720D-HKUA

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Contact spray

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

WAXOYL AG
Seewenweg 5
4153 Reinach / SWITZERLAND
Phone +41-61-28177 94
Fax +41-61-28177 85
Homepage www.waxoyl.com
E-mail info@waxoyl.ch

Address enquiries to

Technical information info@waxoyl.ch

Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Hazard pictograms



Signal word DANGER

Hazard statements
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
P260 Do not breathe vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Human health dangers Contains no ingredients with endocrine-disrupting properties.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
25 - 50	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	EINECS/ELINCS: 918-481-9, Reg-No.: 01-2119457273-39-XXXX
	GHS/CLP: Asp. Tox. 1: H304 - EUH066
< 25	Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based
	CAS: 94733-15-0, EINECS/ELINCS: 305-594-8, Reg-No.: 01-2119486987-11-XXXX
	GHS/CLP: Asp. Tox. 1: H304
< 25	Distillates (petroleum), dewaxed light paraffinic, hydrotreated
	CAS: 91995-40-3, EINECS/ELINCS: 295-301-9, Reg-No.: 01-2119488517-24-XXXX
	GHS/CLP: Asp. Tox. 1: H304
2.5 - 10	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1A: H220 - Press. Gas: H280
10 - 25	Butane
	CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
	GHS/CLP: Flam. Gas 1A: H220 - Press. Gas: H280
10 - 25	iso-Butane
	CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
	GHS/CLP: Flam. Gas 1A: H220 - Press. Gas: H280
< 2.5	2-Butoxyethanol
	CAS: 111-76-2, EINECS/ELINCS: 203-905-0, EU-INDEX: 603-014-00-0, Reg-No.: 01-2119475108-36-XXXX
	GHS/CLP: Acute Tox. 4: H302 H312 H332 - Eye Irrit. 2: H319 - Skin Irrit. 2: H315

Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Remove person to fresh air and keep comfortable for breathing.
In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Drowsiness
Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam.
Dry powder.
Water spray jet.
Carbon dioxide.

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Bursting aerosols can be forcibly projected from a fire.

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Provide suitable vacuuming at the processing area.

Keep away from all sources of ignition - Refrain from smoking.
Vapours can form an explosive mixture with air.

Do not eat, drink, smoke or take drugs at work.
Wash hands before breaks and after work.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.

Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.

Keep in a cool place, heat causes increase in pressure and risk of bursting.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EINECS/ELINCS: 918-481-9, Reg-No.: 01-2119457273-39-XXXX
Long-term exposure: 184 ppm, 1200 mg/m³, ExxonMobil
iso-Butane
CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
Long-term exposure: 600 ppm, 1450 mg/m³, (Butane)
Short-term exposure (15-minute): 750 ppm, 1810 mg/m³
Butane
CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
Long-term exposure: 600 ppm, 1450 mg/m³
Short-term exposure (15-minute): 750 ppm, 1810 mg/m³
Distillates (petroleum), dewaxed light paraffinic, hydrotreated
CAS: 91995-40-3, EINECS/ELINCS: 295-301-9, Reg-No.: 01-2119488517-24-XXXX
Long-term exposure: 5 mg/m³
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based
CAS: 94733-15-0, EINECS/ELINCS: 305-594-8, Reg-No.: 01-2119486987-11-XXXX
Long-term exposure: 5 mg/m³
2-Butoxyethanol
CAS: 111-76-2, EINECS/ELINCS: 203-905-0, EU-INDEX: 603-014-00-0, Reg-No.: 01-2119475108-36-XXXX
Long-term exposure: 25 ppm, 123 mg/m³, Sk, BMGV
Short-term exposure (15-minute): 50 ppm, 246 mg/m³
White mineral oil (petroleum)
CAS: 8042-47-5, EINECS/ELINCS: 232-455-8, Reg-No.: 01-2119487078-27-XXXX
Long-term exposure: 5 mg/m³, oil mist TWA, ACGIH

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
2-Butoxyethanol
CAS: 111-76-2, EINECS/ELINCS: 203-905-0, EU-INDEX: 603-014-00-0, Reg-No.: 01-2119475108-36-XXXX
Eight hours: 20 ppm, 98 mg/m³, H
Short-term (15-minute): 50 ppm, 246 mg/m³

DNEL

Substance
Butane, CAS: 106-97-8
There are no DNEL values established for the substance.
2-Butoxyethanol, CAS: 111-76-2
Industrial, inhalative (vapor), Acute - systemic effects, 1091 mg/m³
Industrial, inhalative (vapor), Acute - local effects, 246 mg/m³
Industrial, inhalative (vapor), Long-term - systemic effects, 98 mg/m³
general population, oral, Long-term - systemic effects, 6.3 mg/kg bw/day
general population, inhalative (vapor), Long-term - systemic effects, 59 mg/m³

general population, inhalative (vapor), Acute - systemic effects, 426 mg/m³
general population, oral, Acute - systemic effects, 26.7 mg/kg bw/day
general population, inhalative (vapor), Acute - local effects, 147 mg/m³
Propane, CAS: 74-98-6
There are no DNEL values established for the substance.
iso-Butane, CAS: 75-28-5
There are no DNEL values established for the substance.
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based, CAS: 94733-15-0
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
There are no DNEL values established for the substance.
Distillates (petroleum), dewaxed light paraffinic, hydrotreated, CAS: 91995-40-3
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day

PNEC

Substance
Butane, CAS: 106-97-8
There are no PNEC values established for the substance.
2-Butoxyethanol, CAS: 111-76-2
soil, 2.33 mg/kg
sediment (seawater), 3.46 mg/kg
sediment (freshwater), 34.6 mg/kg
sewage treatment plants (STP), 463 mg/l
seawater, 0.88 mg/l
freshwater, 8.8 mg/l
oral (food), 0.02 g/kg
Propane, CAS: 74-98-6
There are no PNEC values established for the substance.
iso-Butane, CAS: 75-28-5
There are no PNEC values established for the substance.
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based, CAS: 94733-15-0
oral (food), 9.33 mg/kg
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
There are no PNEC values established for the substance.
Distillates (petroleum), dewaxed light paraffinic, hydrotreated, CAS: 91995-40-3
oral (food), 9.33 mg/kg food

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	0.7mm Butyl rubber, >120 min (EN 374-1/-2/-3). The details concerned are recommendations. Please contact the glove supplier for further information.
Skin protection	Protective clothing (EN 340)
Other	Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, filter AX (DIN EN 14387).
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	aerosol
Color	colourless
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	1.5 Vol.%
Upper explosion limit	8.5 - 10.9 Vol.%
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/cm³]	0.82 (Liquid)
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Solubility other solvents	not required
Partition coefficient [n-octanol/water]	not determined
Kinematic viscosity	not applicable
Relative vapour density	not applicable
Evaporation speed	not applicable
Melting point [°C]	not applicable
Auto-ignition temperature	not applicable
Decomposition temperature [°C]	not applicable
Particle characteristics	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Risk of bursting.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

Flammable gases/vapours.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product
ATE-mix, oral, > 2000 mg/kg

Substance
2-Butoxyethanol, CAS: 111-76-2
LD50, oral, Guinea pig, 1414 mg/kg
LD50, oral, Rat, 1746 mg/kg (OECD 401)
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based, CAS: 94733-15-0
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LD50, oral, Rat, 5000 - 15000 mg/kg bw
Distillates (petroleum), dewaxed light paraffinic, hydrotreated, CAS: 91995-40-3
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)

Acute dermal toxicity

Product
ATE-mix, dermal, > 2000 mg/kg

Substance
2-Butoxyethanol, CAS: 111-76-2
LD50, dermal, Guinea pig, > 2000 mg/kg (OECD 402)
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based, CAS: 94733-15-0
LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 402)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LD50, dermal, Rabbit, 3160 - 5000 mg/kg bw
LD50, dermal, Rat, >2000 mg/kg bw

Acute inhalational toxicity

Product
ATE-mix, inhalation (vapour), > 20 mg/l 4h

Substance
Butane, CAS: 106-97-8
LC50, inhalative, Rat, 658 mg/L (IUCLID)
2-Butoxyethanol, CAS: 111-76-2
LC0, inhalation (vapour), > 3.1 mg/l/1h
Propane, CAS: 74-98-6
LC50, inhalative, Rat, > 1443 mg/l (15 min) (Lit.)
iso-Butane, CAS: 75-28-5
LC50, inhalative, mouse, 1237 mg/L
Lubricating oils (petroleum), C18-40, solvent-dewaxed hydrocracked distillate-based, CAS: 94733-15-0
LC50, inhalative, Rat, 2.18 mg/l air (OECD 403)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LC50, inhalative, Rat, 4.951 - 9.3 mg/L air, 4h

LC50, inhalative, Rat, 41 - 4467 ppm, 8h
LC50, inhalative, Rat, 5 mg/L air, 8h
Distillates (petroleum), dewaxed light paraffinic, hydrotreated, CAS: 91995-40-3
LC50, inhalative, Rabbit, >5000 mg/kg (OECD 402)
LC50, inhalative, Rat, >5.53 mg/l air (OECD 403)

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
Butane, CAS: 106-97-8
Eye, non-irritating
2-Butoxyethanol, CAS: 111-76-2
Study, irritant
Propane, CAS: 74-98-6
Eye, non-irritating
iso-Butane, CAS: 75-28-5
Eye, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
Butane, CAS: 106-97-8
dermal, non-irritating
2-Butoxyethanol, CAS: 111-76-2
Study, irritant
Propane, CAS: 74-98-6
dermal, non-irritating
iso-Butane, CAS: 75-28-5
dermal, non-irritating

Respiratory or skin sensitisation

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
Butane, CAS: 106-97-8
inhalative, non-sensitizing
dermal, non-sensitizing
2-Butoxyethanol, CAS: 111-76-2
dermal, Guinea pig, OECD 406, negativ
Propane, CAS: 74-98-6
inhalative, non-sensitizing
dermal, non-sensitizing
iso-Butane, CAS: 75-28-5
inhalative, non-sensitizing
dermal, non-sensitizing

Specific target organ toxicity — single exposure

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance

Butane, CAS: 106-97-8
inhalative, non-irritating
2-Butoxyethanol, CAS: 111-76-2
inhalative, non-irritating
Propane, CAS: 74-98-6
inhalative, non-irritating
iso-Butane, CAS: 75-28-5
inhalative, non-irritating

Specific target organ toxicity — repeated exposure

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
2-Butoxyethanol, CAS: 111-76-2
LOAEL, oral, Rat, 69 mg/kg bw/day, Study, negativ
LOAEC, inhalative, Rat, 152 mg/m³, Study, negativ
Propane, CAS: 74-98-6
NOAEC, inhalative, Rat, 4437 mg/m³
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
NOAEL, dermal, Rabbit, 2000 mg/kg bw/day
NOAEL, oral, Rat, 500 mg/kg bw/day
NOAEC, inhalative, mouse, 11600 mg/m³
NOAEC, inhalative, Rat, 6000 mg/m³

Mutagenicity

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Reproduction toxicity

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
2-Butoxyethanol, CAS: 111-76-2
NOAEL, oral, Rat, 720 mg/kg bw/day, Study, negativ
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
NOAEC, inhalative, Rat, 5220 mg/m³

Carcinogenicity

Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
2-Butoxyethanol, CAS: 111-76-2
NOAEC, inhalative, Rat, 125 mg/m³, Study, negativ

Aspiration hazard

Based on the available information, the classification criteria are fulfilled.
May be fatal if swallowed and enters airways.

General remarks

The determination of properties hazardous to health does not take the propellant or carrier material into account.

11.2 Information on other hazards

Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

Other information

SECTION 12: Ecological information

12.1 Toxicity

Substance
2-Butoxyethanol, CAS: 111-76-2
LC50, (96h), Oncorhynchus mykiss, 1474 mg/l (OECD 203)
EC50, (48h), Daphnia magna, 1550 mg/l (OECD 202)
EC50, (72h), Pseudokirchneriella subcapitata, 1840 mg/l (OECD 201)
EC0, (16h), Pseudomonas putida, 700 mg/l (DIN 38412)
NOEL, (21d), Brachidanio rerio, > 100 mg/l
NOEL, (21d), Daphnia magna, 100 mg/l (OECD 211)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EL50, (72h), Algae, 1 g/L
NOELR, (28d), fish, 101 µg/L
NOELR, (72h), Algae, 1 g/L
NOELR, (21d), Invertebrates, 176 µg/L
LL50, (96h), fish, 1 g/L
LL50, (72h), fish, 1 g/L
LL50, (48h), fish, 1 g/L
LL50, (24h), fish, 1 g/L
LL50, (24h), Invertebrates, 1 g/L
LL50, (48h), Invertebrates, 1 g/L
LL50, (72h), Invertebrates, 1 g/L
LL50, (96h), Invertebrates, 1 g/L
LL0, (96h), fish, 1 g/L
LL0, (24h), Invertebrates, 1 g/L
Distillates (petroleum), dewaxed light paraffinic, hydrotreated, CAS: 91995-40-3
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, >10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended) 160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.
Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances
150104

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID	1950
Inland navigation (ADN)	1950
Marine transport in accordance with IMDG	1950
Air transport in accordance with IATA	1950

14.2 UN proper shipping name

Transport by land according to ADR/RID	Aerosols
- Classification Code	5F
- Label	
- ADR LQ	1 l
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 2 (D)
Inland navigation (ADN)	Aerosols
- Classification Code	5F
- Label	
Marine transport in accordance with IMDG	Aerosols
- EMS	F-D, S-U
- Label	
- IMDG LQ	1 l
Air transport in accordance with IATA	Aerosols, flammable
- Label	

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	2
Inland navigation (ADN)	2
Marine transport in accordance with IMDG	2.1
Air transport in accordance with IATA	2.1

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2022)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	85%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.
EUH066 Repeated exposure may cause skin dryness or cracking.
H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform ChemicaL Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229 Pressurised container: May burst if heated. (Bridging principle "Aerosols")
Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. (Bridging principle "Aerosols")

Modified position

SECTION 2 been added: Contains no ingredients with endocrine-disrupting properties.

SECTION 2 deleted: P314 Get medical advice / attention if you feel unwell.

SECTION 2 deleted: P280 Wear protective gloves / eye protection / face protection.

SECTION 2 deleted: STOT RE 1

SECTION 2 deleted: H372 Causes damage to organs through prolonged or repeated exposure.

SECTION 2 deleted: health hazard

SECTION 2 deleted: Aquatic Chronic 3

SECTION 2 deleted: H412 Harmful to aquatic life with long lasting effects.

SECTION 8 been added: Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 8 been added: In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection.

Copyright: Chemiebüro®