SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hardwax PF Aerosol

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Corrosion protection

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

WAXOYL AG
Oberwilerstrasse 98
4054 Basel / SWITZERLAND
Phone +41-61-28177 94
Fax +41-61-28177 85
Homepage www.waxoyl.com
E-mail info@waxoyl.ch

Address enquiries to

Technical information info@waxoyl.ch

Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.
STOT SE 3: H336 May cause drowsiness or dizziness.
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Hazard pictograms





Signal word DANGER

Contains: Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C9, aromatics

Hazard statements

H229 Pressurised container: May burst if heated.
H222 Extremely flammable aerosol.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
P261 Avoid breathing vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P312 Call a POISON CENTER / doctor /…/ if you feel unwell.
P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling EUH066 Repeated exposure may cause skin dryness or cracking.

Contains: Sulfonic acids, petroleum, calcium salts. EUH208 May produce an allergic reaction.

2004/42/CE < 840 g/L II B e Special finishes (max. 840 g/l)

2.3 Other hazards

Physico-chemical hazards Vapours can form an explosive mixture with air.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
20 - 30	Butane
	CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
20 - 30	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	EINECS/ELINCS: 927-241-2, Reg-No.: 01-2119471843-32-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - Asp. Tox. 1: H304 - STOT SE 3: H336 - Aquatic Chronic 3: H412
2,5 - 10	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	CAS: 64742-47-8, EINECS/ELINCS: 919-857-5, EU-INDEX: 649-327-00-6, Reg-No.: 01-2119463258-33-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - Asp. Tox. 1: H304 - STOT SE 3: H336
1 - 10	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
1 - <10	Hydrocarbons, C9, aromatics
	EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H335 - Aquatic Chronic 2: H411 - Asp. Tox. 1: H304 - STOT SE 3: H336
1 - <10	Sulfonic acids, petroleum, calcium salts
	CAS: 61789-86-4, EINECS/ELINCS: 263-093-9, Reg-No.: 01-2119488992-18-XXXX
	GHS/CLP: Skin Sens. 1B: H317
1 - <5	iso-Butane
	CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280

Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Remove person to fresh air and keep comfortable for breathing.
In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion Seek medical advice immediately.
Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Drowsiness
Irritant effects
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam.
Dry powder.
Water spray jet.
Carbon dioxide.

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Bursting aerosols can be forcibly projected from a fire.

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Provide suitable vacuuming at the processing area.

Keep away from all sources of ignition - Refrain from smoking.
Vapours can form an explosive mixture with air.

Do not eat, drink, smoke or take drugs at work.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.

Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.

Keep in a cool place, heat causes increase in pressure and risk of bursting.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Butane
CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
Long-term exposure: 600 ppm, 1450 mg/m³
Short-term exposure (15-minute): 750 ppm, 1810 mg/m³
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EINECS/ELINCS: 927-241-2, Reg-No.: 01-2119471843-32-XXXX
Long-term exposure: 100 ppm, 525 mg/m³, OSHA
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
CAS: 64742-47-8, EINECS/ELINCS: 919-857-5, EU-INDEX: 649-327-00-6, Reg-No.: 01-2119463258-33-XXXX
Long-term exposure: 100 ppm, 525 mg/m³, OSHA
iso-Butane
CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
Long-term exposure: 600 ppm, 1450 mg/m³, (Butane)
Short-term exposure (15-minute): 750 ppm, 1810 mg/m³
Hydrocarbons, C9, aromatics
EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
Long-term exposure: 100 mg/m³
Calcium carbonate
CAS: 471-34-1, EINECS/ELINCS: 207-439-9
Long-term exposure: 10 mg/m³, inhalable dust

DNEL

Substance
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Industrial, inhalative, Long-term - systemic effects: 871 mg/m³.
Industrial, dermal, Long-term - systemic effects: 208 mg/kg bw/day.
general population, dermal, Long-term - systemic effects: 125 mg/kg bw/day.
general population, oral, Long-term - systemic effects: 125 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 185 mg/m³.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, CAS: 64742-47-8
Industrial, inhalative (vapor), Long-term - systemic effects: 1500 mg/m³.
Industrial, dermal, Long-term - systemic effects: 300 mg/kg bw/d.
general population, inhalative (vapor), Long-term - systemic effects: 900 mg/m³.
general population, dermal, Long-term - systemic effects: 300 mg/kg bw/d.
general population, oral, Long-term - systemic effects: 300 mg/kg bw/d.
Hydrocarbons, C9, aromatics
Industrial, inhalative (vapor), Long-term - systemic effects: 150 mg/m³.
Industrial, dermal, Long-term - systemic effects: 25 mg/kg.
general population, oral, Long-term - systemic effects: 11 mg/kg.
general population, dermal, Long-term - systemic effects: 11 mg/kg.
general population, inhalative (vapor), Long-term - systemic effects: 32 mg/m³.
Sulfonic acids, petroleum, calcium salts, CAS: 61789-86-4
Industrial, inhalative, Long-term - systemic effects: 11,75 mg/m³.

Industrial, dermal, Long-term - systemic effects: 3,33 mg/kg bw/day.
general population, dermal, Long-term - local effects: 0,513 mg/cm².
general population, oral, Long-term - systemic effects: 0,833 mg/kg bw/day.
general population, dermal, Long-term - systemic effects: 1,667 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 2,9 mg/m³.

PNEC

Substance
Sulfonic acids, petroleum, calcium salts, CAS: 61789-86-4
oral (food), 16,667 mg/kg food.
soil, 271 000 000 mg/kg soil dw.
sediment (seaater), 226 000 000 mg/kg sediment dw.
sediment (freshwater), 226 000 000 mg/kg sediment dw.
sewage treatment plants (STP), 1000 mg/L.
seawater, 1 mg/L.
freshwater, 1 mg/L.

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.
Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.

Eye protection
Safety glasses. (EN 166:2001)

Hand protection
0,4mm Butyl rubber, >120 min (EN 374-1/-2/-3).
The details concerned are recommendations. Please contact the glove supplier for further information.

Skin protection
Protective clothing.

Other
Do not inhale gases/vapours/aerosols.
Avoid contact with eyes and skin.
Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.

Respiratory protection
Respiratory protection mask in the event of high concentrations.
Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)

Thermal hazards
none

Delimitation and monitoring of the environmental exposition
Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	aerosol
Color	beige
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	0,6 Vol.%
Upper explosion limit	11,0 Vol.%
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	350 - 500 (20°C)
Density [g/ml]	~ 0,75 (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	not applicable
Relative vapour density determined in air	not applicable
Evaporation speed	not applicable
Melting point [°C]	not applicable
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapours can form an explosive mixture with air.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Risk of bursting.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

Flammable gases/vapours.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, inhalation (vapour), > 20 mg/l 4h.
ATE-mix, dermal, > 2000 mg/kg.
ATE-mix, oral, > 2000 mg/kg.

Substance
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LD50, dermal, Rabbit: > 5000 mg/kg (OECD 402).
LD50, oral, Rat: > 5000 mg/kg (OECD 401).
LC50, inhalative, Rat: > 4951 mg/m³ (OECD 403).
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, CAS: 64742-47-8
LD50, dermal, Rabbit: > 5000 mg/kg.
LD50, oral, Rat: > 5000 mg/kg.
LC50, inhalative, Rat: > 4951 mg/m³/4h.
Hydrocarbons, C9, aromatics
LD50, dermal, Rabbit: >2000 mg/kg bw (IUCLID).
LD50, oral, Rat: 3500 mg/kg bw (IUCLID).
LC50, inhalative, Rat: >5,2 mg/L (4h) (IUCLID).
iso-Butane, CAS: 75-28-5
LC50, inhalative, mouse: 1237 mg/l (2h) (Lit.).
Propane, CAS: 74-98-6
LC50, inhalative, Rat: > 1443 mg/l (15 min) (Lit.).
Butane, CAS: 106-97-8
LC50, inhalative, Rat: 658 mg/l (4 h) (Lit.).
Sulfonic acids, petroleum, calcium salts, CAS: 61789-86-4
LD50, dermal, Rabbit: > 4000 mg/kg (OECD 402).
LD50, oral, Rat: > 5000 mg/kg (OECD 401).

Serious eye damage/irritation
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Skin corrosion/irritation
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Respiratory or skin sensitisation
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.
No classification due to substance-specific concentration limits.

Specific target organ toxicity — single exposure
Vapours may cause drowsiness and dizziness.
Based on the available information, the classification criteria are fulfilled.
Toxicological data of complete product are not available.

Specific target organ toxicity — repeated exposure
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Mutagenicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Reproduction toxicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Carcinogenicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Aspiration hazard

May be fatal if swallowed and enters airways.
Based on the available information, the classification criteria are fulfilled.

General remarks

The determination of properties hazardous to health does not take the propellant or carrier material into account.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EL50, (72h), Pseudokirchneriella subcapitata: > 1000 mg/l.
EL50, (48h), Daphnia magna: 22 - 46 mg/l.
NOELR, (72h), Pseudokirchneriella subcapitata: < 1 mg/l.
LL50, (96h), Oncorhynchus mykiss: 10 - 30 mg/l.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, CAS: 64742-47-8
EL0, (48h), Daphnia magna: 1000 mg/l.
EL50, (72h), Algae: > 1000 mg/l.
NOELR, (72h), Algae: 100 mg/l.
LL50, (96h), Oncorhynchus mykiss: > 1000 mg/l.
Hydrocarbons, C9, aromatics
LC50, (96h), Oncorhynchus mykiss: 9,22 mg/L (IUCLID).
EC50, (72h), Selenastrum capricornutum: 56 mg/L (IUCLID).
EC50, (48h), Daphnia magna: 6,14 mg/L (IUCLID).
Sulfonic acids, petroleum, calcium salts, CAS: 61789-86-4
LC50, (96h), fish: > 10.000 mg/l (OECD 203).
EC50, (3h), Activated sludge: > 10.000 mg/l (OECD 209).

12.2 Persistence and degradability

Behaviour in environment compartments not determined

Behaviour in sewage plant not determined

Biological degradability not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended) 160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.
Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150110*
150104

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID	1950
Inland navigation (ADN)	1950
Marine transport in accordance with IMDG	1950
Air transport in accordance with IATA	1950

14.2 UN proper shipping name

Transport by land according to ADR/RID	Aerosols
- Classification Code	5F
- Label	
- ADR LQ	1 l
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 2 (D)
Inland navigation (ADN)	Aerosols
- Classification Code	5F
- Label	
Marine transport in accordance with IMDG	Aerosols
- EMS	F-D, S-U
- Label	
- IMDG LQ	1 l
Air transport in accordance with IATA	Aerosols, flammable
- Label	

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	2
Inland navigation (ADN)	2
Marine transport in accordance with IMDG	2.1
Air transport in accordance with IATA	2.1

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2018).
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	80 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform ChemicaL Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229
Pressurised container: May burst if heated. (Bridging principle "Aerosols")
Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. (Bridging principle "Aerosols")
STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

none

Copyright: Chemiebüro®