SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silencer Coating silver
UFI: SK6K-UYWF-E10T-NYDE

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Paint

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

WAXOYL AG
Seewenweg 5
4153 Reinach / SWITZERLAND
Phone +41-61-28177 94
Fax +41-61-28177 85
Homepage www.waxoyl.com
E-mail info@waxoyl.ch

Address enquiries to

Technical information info@waxoyl.ch

Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
Eye Irrit. 2: H319 Causes serious eye irritation.
STOT SE 3: H336 May cause drowsiness or dizziness.
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Hazard pictograms




Signal word DANGER

Contains: Acetone

Hazard statements

H229 Pressurised container: May burst if heated.
H222 Extremely flammable aerosol.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
P280 Wear protective gloves / eye protection / face protection.
P261 Avoid breathing vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P337+P313 If eye irritation persists: Get medical advice / attention.
P312 Call a POISON CENTER / doctor if you feel unwell.
P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Human health dangers Contains no ingredients with endocrine-disrupting properties.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - 40	Acetone
	CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336 - EUH066
15 - 30	iso-Butane
	CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
1 - 10	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
1 - 10	n-Butyl acetate
	CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H336 - EUH066
1 - < 10	2-Methoxy-1-methylethyl acetate
	CAS: 108-65-6, EINECS/ELINCS: 203-603-9, EU-INDEX: 607-195-00-7, Reg-No.: 01-2119475791-29-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H336
1 - <= 6	Reaction mass of ethylbenzene and xylene
	EINECS/ELINCS: 905-588-0, Reg-No.: 01-2119488216-32-XXXX, 01-2119486136-34-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - Acute Tox. 4: H312 H332 - Asp. Tox. 1: H304 - Skin Irrit. 2: H315 - Eye Irrit. 2: H319 - STOT SE 3: H335 - STOT RE 2: H373
	SCL [%]: >= 10: STOT RE 2: H373
< 5	Aluminium
	CAS: 7429-90-5, EINECS/ELINCS: 231-072-3, EU-INDEX: 013-002-00-1, Reg-No.: 01-2119529243-45-XXXX
	GHS/CLP: Flam. Sol. 1: H228 - Water-react. 2: H261
2,5 - < 5	Hydrocarbons, C9, aromatics
	EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H335 - Aquatic Chronic 2: H411 - Asp. Tox. 1: H304 - STOT SE 3: H336 - EUH066

Comment on component parts contains silicones.
Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Drowsiness
Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam.
Dry powder.
Water spray jet.
Carbon dioxide.

Extinguishing media that must not be used Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Bursting aerosols can be forcibly projected from a fire.

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Provide suitable vacuuming at the processing area.

Keep away from all sources of ignition - Refrain from smoking.
Vapours can form an explosive mixture with air.

Do not eat, drink, smoke or take drugs at work.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.

Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.

Keep in a cool place, heat causes increase in pressure and risk of bursting.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Long-term exposure: 500 ppm, 1210 mg/m³
Short-term exposure (15-minute): 1500 ppm, 3620 mg/m³
Hydrocarbons, C9, aromatics
EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
Long-term exposure: 100 mg/m³
iso-Butane
CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
Long-term exposure: 600 ppm, 1450 mg/m³, (Butane)
Short-term exposure (15-minute): 750 ppm, 1810 mg/m³
n-Butyl acetate
CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
Long-term exposure: 150 ppm, 724 mg/m³
Short-term exposure (15-minute): 200 ppm, 966 mg/m³
2-Methoxy-1-methylethyl acetate
CAS: 108-65-6, EINECS/ELINCS: 203-603-9, EU-INDEX: 607-195-00-7, Reg-No.: 01-2119475791-29-XXXX
Long-term exposure: 50 ppm, 274 mg/m³, Sk
Short-term exposure (15-minute): 100 ppm, 548 mg/m³
Xylene, mixture of isomers
CAS: 1330-20-7, EINECS/ELINCS: 215-535-7, EU-INDEX: 601-022-00-9, Reg-No.: 01-2119488216-32-XXXX
Long-term exposure: 50 ppm, 220 mg/m³, Sk, BMGV
Short-term exposure (15-minute): 100 ppm, 441 mg/m³
Aluminium
CAS: 7429-90-5, EINECS/ELINCS: 231-072-3, EU-INDEX: 013-002-00-1, Reg-No.: 01-2119529243-45-XXXX
Long-term exposure: 10 mg/m³, inhalable dust (respirable dust: 4 mg/m³)
Ethylbenzene
CAS: 100-41-4, EINECS/ELINCS: 202-849-4, EU-INDEX: 601-023-00-4, Reg-No.: 01-2119489370-35-XXXX
Long-term exposure: 100 ppm, 441 mg/m³, Sk
Short-term exposure (15-minute): 125 ppm, 552 mg/m³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Eight hours: 500 ppm, 1210 mg/m³
n-Butyl acetate
CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
Eight hours: 50 ppm, 241 mg/m³
Short-term (15-minute): 150 ppm, 723 mg/m³
2-Methoxy-1-methylethyl acetate
CAS: 108-65-6, EINECS/ELINCS: 203-603-9, EU-INDEX: 607-195-00-7, Reg-No.: 01-2119475791-29-XXXX

Eight hours: 50 ppm, 275 mg/m³, H
Short-term (15-minute): 100 ppm, 550 mg/m³
Xylene, mixture of isomers
CAS: 1330-20-7, EINECS/ELINCS: 215-535-7, EU-INDEX: 601-022-00-9, Reg-No.: 01-2119488216-32-XXXX
Eight hours: 50 ppm, 221 mg/m³, H
Short-term (15-minute): 100 ppm, 442 mg/m³
Ethylbenzene
CAS: 100-41-4, EINECS/ELINCS: 202-849-4, EU-INDEX: 601-023-00-4, Reg-No.: 01-2119489370-35-XXXX
Eight hours: 100 ppm, 442 mg/m³, H
Short-term (15-minute): 200 ppm, 884 mg/m³

DNEL

Substance
Aluminium, CAS: 7429-90-5
Industrial, inhalative, Long-term - systemic effects, 3,72 mg/m³
Industrial, inhalative, Long-term - local effects, 3,72 mg/m³
general population, oral, Long-term - systemic effects, 7,9 mg/kg bw/day
Reaction mass of ethylbenzene and xylene
Industrial, inhalative (vapor), Long-term - systemic effects, 221 mg/m³
Industrial, inhalative (vapor), Acute - systemic effects, 442 mg/m³
Industrial, inhalative (vapor), Long-term - local effects, 221 mg/m³
Industrial, inhalative (vapor), Acute - local effects, 442 mg/m³
Industrial, dermal, Long-term - systemic effects, 212 mg/kg bw/day
general population, inhalative (vapor), Acute - systemic effects, 260 mg/m³
general population, oral, Long-term - systemic effects, 12,5 mg/kg bw/day
general population, dermal, Acute - local effects, 125 mg/kg bw/day
general population, inhalative (vapor), Long-term - local effects, 65,3 mg/m³
general population, inhalative (vapor), Long-term - systemic effects, 65,3 mg/m³
general population, inhalative (vapor), Acute - local effects, 260 mg/m³
n-Butyl acetate, CAS: 123-86-4
Industrial, inhalative (vapor), Acute - local effects, 600 mg/m³
Industrial, inhalative (vapor), Long-term - local effects, 300 mg/m³
Industrial, inhalative (vapor), Acute - systemic effects, 600 mg/m³
Industrial, dermal, Long-term - systemic effects, 11 mg/kg bw/day
Industrial, dermal, Acute - systemic effects, 11 mg/kg bw/day
Industrial, inhalative (vapor), Long-term - systemic effects, 300 mg/m³
general population, dermal, Acute - systemic effects, 6 mg/kg bw/day
general population, inhalative (vapor), Long-term - systemic effects, 35,7 mg/m³
general population, inhalative (vapor), Acute - systemic effects, 300 mg/m³
general population, inhalative (vapor), Long-term - local effects, 35,7 mg/m³
general population, dermal, Long-term - systemic effects, 6 mg/kg bw/day
general population, oral, Long-term - systemic effects, 2 mg/kg bw/day
general population, oral, Acute - systemic effects, 2 mg/kg bw/day
general population, inhalative (vapor), Acute - local effects, 300 mg/m³
Acetone, CAS: 67-64-1
Industrial, inhalative, Long-term - systemic effects, 1210 mg/m³
Industrial, inhalative, Long-term - local effects, 2420 mg/m³
Industrial, dermal, Long-term - systemic effects, 186 mg/kg bw/d

general population, oral, Long-term - systemic effects, 62 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 62 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 200 mg/m³
Hydrocarbons, C9, aromatics, CAS: 128601-23-0
Industrial, dermal, Long-term - systemic effects, 25 mg/kg/d
Industrial, inhalative, Long-term - systemic effects, 150 mg/m³
general population, oral, Long-term - systemic effects, 11 mg/kg bw/d
general population, dermal, Long-term - systemic effects, 11 mg/kg/d
general population, inhalative, Long-term - systemic effects, 32 mg/m³
2-Methoxy-1-methylethyl acetate, CAS: 108-65-6
Industrial, inhalative, Acute - local effects, 550 mg/m³
Industrial, inhalative, Long-term - systemic effects, 275 mg/m³
Industrial, dermal, Long-term - systemic effects, 796 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 320 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 33 mg/m³
general population, oral, Long-term - systemic effects, 36 mg/kg bw/day
general population, inhalative, Long-term - local effects, 33 mg/m³

PNEC

Substance
Reaction mass of ethylbenzene and xylene
sediment (seawater), 12,46 mg/kg sediment dw
sediment (freshwater), 12,46 mg/kg sediment dw
sewage treatment plants (STP), 6,58 mg/L
seawater, 0,327 mg/L
freshwater, 0,327 mg/L
soil, 2,31 mg/kg soil dw
n-Butyl acetate, CAS: 123-86-4
seawater, 0,018 mg/L (AF= 1000)
sewage treatment plants (STP), 35,6 mg/L (AF= 10)
sediment (freshwater), 0,981 mg/kg/ dw
sediment (seawater), 0,098 mg/kg/ dw
soil, 0,09 mg/kg/ dw
freshwater, 0,18 mg/L (AF= 100)
Acetone, CAS: 67-64-1
soil, 29,5 mg/kg
freshwater, 10,6 mg/l
seawater, 1,06 mg/l
sewage treatment plants (STP), 100 mg/l
sediment (freshwater), 30,4 mg/kg
sediment (seawater), 3,04 mg/kg
2-Methoxy-1-methylethyl acetate, CAS: 108-65-6
seawater, 0,064 mg/L
sediment (freshwater), 3,29 mg/kg sediment dw
sediment (seawater), 0,329 mg/kg sediment dw
soil, 0,29 mg/kg soil dw
sewage treatment plants (STP), 100 mg/L
freshwater, 0,635 mg/L

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	0,4mm Butyl rubber, >120 min (EN 374-1/-2/-3). The details concerned are recommendations. Please contact the glove supplier for further information.
Skin protection	Protective clothing (EN 340)
Other	Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	aerosol
Color	silver
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	ca. 1,5 Vol.%
Upper explosion limit	ca. 13 Vol.%
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	
Density [g/ml]	0,87 (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	not determined
Kinematic viscosity	not applicable
Relative vapour density	not applicable
Evaporation speed	not applicable
Melting point [°C]	not applicable
Auto-ignition temperature	not applicable
Decomposition temperature [°C]	not applicable
Particle characteristics	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Risk of bursting.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

Flammable gases/vapours.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Product
ATE-mix, oral, > 2000 mg/kg

Substance
Aluminium, CAS: 7429-90-5
LD50, oral, Rat, > 15900 mg/kg bw
Reaction mass of ethylbenzene and xylene
LD50, oral, Rat, 3523 - 4000 mg/kg
n-Butyl acetate, CAS: 123-86-4
LD50, oral, Rat, 10760 mg/kg (OECD 423)
Acetone, CAS: 67-64-1
LD50, oral, Rat, 5800 mg/kg (OECD 401)
Hydrocarbons, C9, aromatics, CAS: 128601-23-0
LD50, oral, Rat, 3592 mg/kg (OECD 401)
2-Methoxy-1-methylethyl acetate, CAS: 108-65-6
LD50, oral, Rat, > 5000 mg/kg

Acute dermal toxicity

Product
ATE-mix, dermal, > 2000 mg/kg

Substance
Reaction mass of ethylbenzene and xylene
LD50, dermal, Rabbit, 12126 mg/kg
n-Butyl acetate, CAS: 123-86-4
LD50, dermal, Rabbit, >14112 mg/kg (OECD 402)
Acetone, CAS: 67-64-1
LD50, dermal, Rabbit, > 15800 mg/kg
Hydrocarbons, C9, aromatics, CAS: 128601-23-0
LD50, dermal, Rabbit, > 3160 mg/kg (OECD 402)
2-Methoxy-1-methylethyl acetate, CAS: 108-65-6
LD50, dermal, Rat, > 2000 mg/kg

Acute inhalational toxicity

Product
ATE-mix, inhalation (vapour), > 20 mg/l 4h

Substance
Reaction mass of ethylbenzene and xylene
LC50, inhalation (vapour), Rat, 6350 - 6700 ppm 4h
iso-Butane, CAS: 75-28-5
LC50, inhalative, mouse, 1237 mg/l (2h) (Lit.)
Propane, CAS: 74-98-6
LC50, inhalative, Rat, > 1443 mg/l (15 min) (Lit.)

n-Butyl acetate, CAS: 123-86-4
LC50, inhalative, Rat, 23,4 mg/l (4h) (OECD 403)
Acetone, CAS: 67-64-1
LC50, inhalative, Rat, 76 mg/l (4h)

Serious eye damage/irritation
Irritant
Based on the available information, the classification criteria are fulfilled.
Toxicological data of complete product are not available.
Calculation method

Skin corrosion/irritation
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Respiratory or skin sensitisation
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Specific target organ toxicity — single exposure
Vapours may cause drowsiness and dizziness.
Based on the available information, the classification criteria are fulfilled.
Toxicological data of complete product are not available.
Calculation method

Specific target organ toxicity — repeated exposure
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Substance
iso-Butane, CAS: 75-28-5
NOAEC, inhalative, Rat, 4437 mg/m³
Propane, CAS: 74-98-6
NOAEC, inhalative, Rat, 4437 mg/m³

Mutagenicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Reproduction toxicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Carcinogenicity
Does not contain a relevant substance that meets the classification criteria.
Based on the available information, the classification criteria are not fulfilled.
Toxicological data of complete product are not available.

Aspiration hazard
Based on the available information, the classification criteria are not fulfilled.

General remarks

The determination of properties hazardous to health does not take the propellant or carrier material into account.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Aluminium, CAS: 7429-90-5
NOEC, (96h), Lepomis macrochirus, > 50 mg/l
Reaction mass of ethylbenzene and xylene
LC50, (24h), Daphnia magna, 1 mg/l OECD 202
LC50, (96h), Oncorhynchus mykiss, 2,6 mg/l OECD 203
EC50, (72h), Selenastrum capricornutum, 2,2 mg/l OECD 201
n-Butyl acetate, CAS: 123-86-4
LC50, (96h), Pimephales promelas, 18 mg/l (OECD 203)
EC50, (48h), Daphnia magna, 44 mg/l
EC50, (72h), Desmodesmus subspicatus, 647,7 mg/l
IC50, Bacteria, 356 mg/l (40 h)
NOEC, Desmodesmus subspicatus, 200 mg/l
Acetone, CAS: 67-64-1
LC50, (48h), Daphnia pulex, 8800 mg/l
LC50, (96h), Oncorhynchus mykiss, 5540 mg/l
NOEC, (96h), Algae, 430 mg/l
Hydrocarbons, C9, aromatics, CAS: 128601-23-0
EL50, (48h), Daphnia magna, 3,2 mg/l (Lit.)
EL50, (72h), Pseudokirchneriella subcapitata, 2,6 - 2,9 mg/l (Lit.)
LL50, (96h), Oncorhynchus mykiss, 9,2 mg/l (Lit.)
2-Methoxy-1-methylethyl acetate, CAS: 108-65-6
LC50, (96h), Oncorhynchus mykiss, 134 mg/l (OECD 203)
EC50, (48h), Daphnia magna, > 500 mg/l
EC50, (72h), Selenastrum capricornutum, > 1000 mg/l (OECD 201)
NOEC, Oryzias latipes, 47,5 mg/l (14 d) (OECD 204)
NOEC, (21d), Daphnia magna, ≥ 100 mg/l (OECD 202)
EC10, Bacteria, > 1000 mg/l (0,5 h) (ISO 8192)

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended) 160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.
Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances
150104

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID	1950
Inland navigation (ADN)	1950
Marine transport in accordance with IMDG	1950
Air transport in accordance with IATA	1950

14.2 UN proper shipping name

Transport by land according to ADR/RID	Aerosols
- Classification Code	5F
- Label	
- ADR LQ	1 l
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 2 (D)
Inland navigation (ADN)	Aerosols
- Classification Code	5F
- Label	
Marine transport in accordance with IMDG	Aerosols
- EMS	F-D, S-U
- Label	
- IMDG LQ	1 l
Air transport in accordance with IATA	Aerosols, flammable
- Label	

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	2
Inland navigation (ADN)	2
Marine transport in accordance with IMDG	2.1
Air transport in accordance with IATA	2.1

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2021)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	89 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H261 In contact with water releases flammable gases.
H228 Flammable solid.

H373 May cause damage to organs through prolonged or repeated exposure through inhalation.
H315 Causes skin irritation.
H312+H332 Harmful in contact with skin or if inhaled.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
H335 May cause respiratory irritation.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.
EUH066 Repeated exposure may cause skin dryness or cracking.
H336 May cause drowsiness or dizziness.
H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform ChemicaL Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229 Pressurised container: May burst if heated. (Bridging principle "Aerosols")
Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)
STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)
Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

SECTION 2 been added: Contains no ingredients with endocrine-disrupting properties.

SECTION 2 been added: H412 Harmful to aquatic life with long lasting effects.

SECTION 2 been added: Aquatic Chronic 3

SECTION 3 been added: contains silicones.

SECTION 8 been added: In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection.

Copyright: Chemiebüro®